

SIDING PRODUCT DIRECTORY

March 2026



Siding • Soffit and Fascia • Trim Accessories



GENTEK®

GENTEK PRODUCT DIRECTORY


	COMPOSITE CLADDING
4	ALIGN
	VINYL SIDING
5	SEQUOIA SELECT
6	BOARD & BATTEN
7	FAIR OAKS
8	CONCORD
10	DRIFTWOOD II
11	SELECTION II
	VINYL SOFFIT AND ACCESSORIES
12	OXFORD Premium Soffit
13	EZ LOCK Soffit
14	BEADED PREMIUM Soffit
15	FAIRWEATHER Soffit
16	ALIGN Composite Accessories
20	Vinyl Accessories
	ALUMINUM SIDING
26	DELUXE
28	WOODGRAIN 2000
	ALUMINUM SOFFIT, FASCIA AND ACCESSORIES
30	Aluminum Soffit
33	Aluminum Fascia
36	Aluminum Accessories
	STEEL SIDING
41	SIERRA STEEL
42	STEELSIDE
	STEEL ACCESSORIES
43	Steel Accessories
	FLATSTOCK
45	Steel Flatstock
46	Aluminum Flatstock
	GUTTER COIL
48	Aluminum Gutter Coil
	COLOUR MATRIX
50	ALIGN Cladding
52	Vinyl Siding and Soffit
54	Vinyl Accessories
56	Aluminum Siding
57	Steel Siding, Accessories, Flatstock
58	Aluminum Soffit and Fascia
60	Aluminum Accessories, Flatstock, Gutter Coil
63	James Hardie Colour Match Trim, CanExel
	ARCHITECTURAL SPECIFICATIONS
64	Vinyl Architectural Specifications
66	Aluminum Architectural Specifications
67	Steel Architectural Specifications
68	Composite Cladding Architectural Specifications
69	Colour Palettes

Not all products are available in all markets.

PRODUCT CODE & DESCRIPTION

COLOURS

CP700
7" Plank




3/8" Butt (9.5 mm)
Panel Projection 3/4" (19 mm)
7" Exposure per Panel (177.8 mm)
12'3" Length (3733.8 mm)
Cedar Mill Grain Texture

Packaging:
14 pcs. per ctn.
1 sq. per ctn. (9.2 m²)

Snow White
Almond
Chesapeake Gray
Coastal Blue
Dark Drift
Dover Gray
Hudson Slate
Iron Ore
Majestic Brick
Marine Dusk
Meadow Fern
Midnight Surf
Monterey Sand
Moonlit Moss
Pebble
Rockport Brown
Rockwell Blue
Smoked Timber
Storm
Windswept Smoke

CP701 (Cedar Mill Grain)
CP702 (Matte)
12" Board & Batten



2" Batten Width (50.8 mm)
Panel Projection 3/4" (19 mm)
12" Exposure per Panel (304.8 mm)
12' Length (3658 mm)
Cedar Mill Grain Texture
Matte Texture

Packaging:
8 pcs. per ctn.
0.96 sq. per ctn. (8.9 m²)


**For ALIGN accessories,
see pages 16-19.**

PRODUCT CODE & DESCRIPTION

COLOURS

64496

Double 4" Clapboard



3/4" Butt (19 mm)
2-4" Exposure per Panel
(101.6/203.2 mm)
12'6" Length (3810 mm)
.046" Nominal Thickness
Cedargrain Texture


Packaging:
24 pcs. per ctn.
2 sqs. per ctn. (18.6 m²)

Snow White

Almond
Dover Gray
Linen
Maize
Monterey Sand
Pearl
Sandstone

64495

Double 4-1/2" Dutch Lap



3/4" Butt (19 mm)
2-4-1/2" Exposure per Panel
(114.5/229 mm)
12'1" Length (3683 mm)
.046" Nominal Thickness
Cedargrain Texture

Packaging:
22 pcs. per ctn.
2 sqs. per ctn. (18.6 m²)


Canyon Clay
Chesapeake Gray
Juniper Grove
Pebble
Sage
Storm
Wicker

DESIGNER COLOURS

Coastal Blue[†]
Dark Drift[†]
Espresso[†]
Hudson Slate[†]
Iron Ore[†]
Majestic Brick[†]
Marine Dusk[†]
Meadow Fern[†]
Midnight Surf[†]
Moonlit Moss[†]
Rockport Brown[†]
Rockwell Blue[†]
Smoked Timber[†]
Windswept Smoke[†]

64497

Double 5" Clapboard




3/4" Butt (19 mm)
2-5" Exposure per Panel
(127/254 mm)
12' Length (3658 mm)
.046" Nominal Thickness
Cedargrain Texture

Packaging:
20 pcs. per ctn.
2 sqs. per ctn. (18.6 m²)

64507

Double 5" Dutch Lap



3/4" Butt (19 mm)
2-5" Exposure per Panel
(127/254 mm)
12' Length (3658 mm)
.046" Nominal Thickness
Cedargrain Texture


Packaging:
20 pcs. per ctn.
2 sqs. per ctn. (18.6 m²)

[†]Designer Colour; Double 5" Clapboard and Double 5" Dutch Lap not available in Designer Colours in British Columbia and Alberta.

PRODUCT CODE & DESCRIPTION

64397

7" Board & Batten



1/2" Batten Height (12.7 mm)
 1-5/8" Batten Width (41.3 mm)
 7" Exposure per Panel (178.5 mm)
 10' Length +/- 1/4"
 (3048 +/- 25.4 mm)
 .050" Nominal Thickness
 Light Roughsawn Texture

Packaging:
 17 pcs. per ctn.
 1 sq. per ctn. (9.2 m²)

COLOURS

Snow White

Almond

Dover Gray

Linen

Maize

Monterey Sand

Pearl

Sandstone

Canyon Clay

Chesapeake Gray

Juniper Grove

Pebble

Sage

Storm

Wicker

DESIGNER COLOURS

Coastal Blue†

Dark Drift†

Espresso†

Hudson Slate†

Iron Ore†

Majestic Brick†

Marine Dusk†

Meadow Fern†

Midnight Surf†

Moonlit Moss†

Rockport Brown†

Rockwell Blue†

Smoked Timber†

Windswept Smoke†

†Designer Colour; not available in British Columbia and Alberta.




PRODUCT CODE & DESCRIPTION

COLOURS

64695

Double 4" Clapboard



5/8" Butt (15.9 mm)
2-4" Exposure per Panel
(101.6/203.2 mm)
12'6" Length (3810 mm)
.044" Nominal Thickness
Hardwood Texture


Packaging:
24 pcs. per ctn.
2 sqs. per ctn. (18.6 m²)

Snow White

- Almond
- Dover Gray
- Linen
- Maize
- Monterey Sand
- Pearl
- Sandstone

64696

Double 4" Dutch Lap




5/8" Butt (15.9 mm)
2-4" Exposure per Panel
(101.6/203.2 mm)
12'6" Length (3810 mm)
.044" Nominal Thickness
Hardwood Texture

Packaging:
24 pcs. per ctn.
2 sqs. per ctn. (18.6 m²)

- Canyon Clay
- Chesapeake Gray
- Juniper Grove
- Pebble
- Sage
- Storm
- Wicker

64697

Double 5" Clapboard



5/8" Butt (15.9 mm)
2-5" Exposure per Panel
(127/254 mm)
12' Length (3658 mm)
.044" Nominal Thickness
Hardwood Texture

Packaging:
20 pcs. per ctn.
2 sqs. per ctn. (18.6 m²)


DESIGNER COLOURS

- Dark Drift†
- Hudson Slate†
- Majestic Brick†
- Meadow Fern†
- Midnight Surf†
- Moonlit Moss†
- Rockport Brown†
- Rockwell Blue†
- Windswept Smoke†

†Designer Colour; Double 5" Clapboard and Double 5" Dutch Lap not available in Designer Colours in British Columbia and Alberta.

64698

Double 5" Dutch Lap



5/8" Butt (15.9 mm)
2-5" Exposure per Panel
(127/254 mm)
12' Length (3658 mm)
.044" Nominal Thickness
Hardwood Texture

Packaging:
20 pcs. per ctn.
2 sqs. per ctn. (18.6 m²)




PRODUCT CODE & DESCRIPTION

COLOURS

64686

Double 4" Clapboard



1/2" Butt (12.7 mm)
 2-4" Exposure per Panel
 (101.6/203.2 mm)
 12'6" Length (3810 mm)
 .042" Nominal Thickness
 Light Roughsawn Texture


Packaging:
 24 pcs. per ctn.
 2 sqs. per ctn. (18.6 m²)

Snow White

Almond
 Dover Gray
 Linen
 Maize
 Monterey Sand
 Pearl
 Sandstone

64621

Double 4" Dutch Lap




1/2" Butt (12.7 mm)
 2-4" Exposure per Panel
 (101.6/203.2 mm)
 12'6" Length (3810 mm)
 .042" Nominal Thickness
 Light Roughsawn Texture

Packaging:
 24 pcs. per ctn.
 2 sqs. per ctn. (18.6 m²)

Canyon Clay
 Chesapeake Gray
 Juniper Grove
 Pebble
 Sage
 Storm
 Wicker

62317

Double 5" Clapboard




5/8" Butt (15.9 mm)
 2-5" Exposure per Panel
 (127/254 mm)
 12' Length (3658 mm)
 .042" Nominal Thickness
 Light Roughsawn Texture

Packaging:
 20 pcs. per ctn.
 2 sqs. per ctn. (18.6 m²)

62215

Double 5" Dutch Lap




7/16" Butt (11.1 mm)
 2-5" Exposure per Panel
 (127/254 mm)
 12' Length (3658 mm)
 .042" Nominal Thickness
 Light Roughsawn Texture

Packaging:
 20 pcs. per ctn.
 2 sqs. per ctn. (18.6 m²)

PRODUCT CODE & DESCRIPTION

64755
10" Vertical



10" Exposure per Panel (254 mm)
12' Length (3658 mm)
.042" Nominal Thickness
Light Roughsawn Texture

Packaging:
24 pcs. per ctn.
2 sqs. per ctn. (18.6 m²)

COLOURS

Snow White

Almond

Dover Gray

Linen

Maize

Monterey Sand

Pearl

Sandstone

Canyon Clay

Chesapeake Gray

Juniper Grove

Pebble

Sage

Storm

Wicker




DRIFTWOOD® II | VINYL SIDING

PRODUCT CODE & DESCRIPTION

62450

Double 4" Clapboard



7/16" Butt (11.1 mm)
2-4" Exposure per Panel
(101.6/203.2 mm)
12'6" Length (3810 mm)
.040" Nominal Thickness
Natural Cedargrain Texture

Packaging:
24 pcs. per ctn.
2 sqs. per ctn. (18.6 m²)

COLOURS

Snow White

Almond

Amber

Dover Gray

Linen

Maize


Monterey Sand

Pearl

Sandstone

62452

Double 4-1/2" Dutch Lap



1/2" Butt (12.7 mm)
2-4-1/2" Exposure per Panel
(114.5/229 mm)
12'1" Length (3683 mm)
.040" Nominal Thickness
Natural Cedargrain Texture

Packaging:
22 pcs. per ctn.
2 sqs. per ctn. (18.6 m²)

Canyon Clay

Chesapeake Gray

Juniper Grove

Pebble

Sage

Storm

Wicker




SELECTION II | VINYL SIDING

PRODUCT CODE & DESCRIPTION

COLOURS

64271

Double 4" Dutch Lap




7/16" (11.1 mm)
2-4" Exposure per Panel
(101.6/203.2 mm)
12'6" Length (3810 mm)
.040" Nominal Thickness
Natural Cedargrain Texture

Packaging:
24 pcs. per ctn.
2 sqs. per ctn. (18.6 m²)

Snow White

64272

Double 5" Dutch Lap



7/16" (11.1 mm)
2-5" Exposure per Panel
(127/254 mm)
12' Length (3658 mm)
.040" Nominal Thickness
Natural Cedargrain Texture


Packaging:
20 pcs. per ctn.
2 sqs. per ctn. (18.6 m²)

PRODUCT CODE & DESCRIPTION

COLOURS

64751
10" D-5
**Solid Soffit/
 Vertical Siding**

10" Exposure per Panel (254 mm)
 10' Length (3048 mm)
 .042" Nominal Thickness
 Light Roughsawn Texture



Packaging:
 24 pcs. per ctn.
 2 sqs. per ctn. (18.6 m²)

Snow White


Almond
 Dover Gray

Linen
 Maize
 Monterey Sand
 Pearl
 Sandstone

Canyon Clay
 Chesapeake Gray
 Juniper Grove
 Pebble
 Sage
 Storm
 Wicker

64754
10" D-5
Fully Vented Soffit

10" Exposure per Panel (254 mm)
 12' Length (3658 mm)
 .042" Nominal Thickness
 Light Roughsawn Texture
 5.3 sq. in. ventilation per lineal ft.



Packaging:
 20 pcs. per ctn.
 2 sqs. per ctn. (18.6 m²)

Black[†]
 Musket Brown[†]


[†]Designer Colour;
 soffit use only.

PRODUCT CODE & DESCRIPTION

COLOURS

64885
EZ Lock
8" Solid Soffit

8" Exposure per Panel (203.2 mm)
12'6" Length (3810 mm)
.041" Nominal Thickness
Light Roughsawn Texture



Packaging:
24 pcs. per ctn.
2 sqs. per ctn. (18.6 m²)

Snow White

Linen


Wicker

Black†

†Designer Colour;
soffit use only.

64880
EZ Lock
8" Vented Soffit

8" Exposure per Panel (203.2 mm)
12'6" Length (3810 mm)
.041" Nominal Thickness
Light Roughsawn Texture
5.3 sq. in. ventilation per lineal ft.



Packaging:
24 pcs. per ctn.
2 sqs. per ctn. (18.6 m²)


BEADED PREMIUM VINYL SOFFIT

PRODUCT CODE & DESCRIPTION

COLOURS

64370

8" Solid Soffit*



8" Exposure per Panel (203.2 mm)
12'6" Length (3810 mm)
.042" Nominal Thickness
Matte Texture

Packaging:
12 pcs. per ctn.
1 sq. per ctn. (9.29 m²)

*Soffit use only.

Snow White

Linen

Monterey Sand


Canyon Clay

Pebble

Wicker

64375

8" Vented Soffit



8" Exposure per Panel (203.2 mm)
12'6" Length (3810 mm)
.042" Nominal Thickness
Matte Texture
2.4 sq. in. ventilation per lineal ft.


Packaging:
12 pcs. per ctn.
1 sq. per ctn. (9.29 m²)

PRODUCT CODE & DESCRIPTION

COLOURS

64456

**12" T-4
Solid Soffit/
Vertical Siding**



12" Exposure per Panel (304.8 mm)
12' Length (3658 mm)
.040" Nominal Thickness
1/2" Nominal Panel Projection
Brushed Texture


Packaging:
16 pcs. per ctn.
1.92 sqs. per ctn. (17.8 m²)

Snow White

Almond
Dover Gray
Linen
Maize
Monterey Sand
Pearl
Sandstone

64458

**12" T-4
Fully Vented Soffit**



12" Exposure per Panel (304.8 mm)
12' Length (3658 mm)
.040" Nominal Thickness
1/2" Nominal Panel Projection
Brushed Texture
7.1 sq. in. ventilation per lineal ft.

Packaging:
16 pcs. per ctn.
1.92 sqs. per ctn. (17.8 m²)

Canyon Clay
Chesapeake Gray
Juniper Grove
Pebble
Sage
Storm
Wicker

Musket Brown†


†Designer Colour;
soffit use only.

PRODUCT CODE & DESCRIPTION**COLOURS**

CP003
**5-1/2" ALIGN
 H-Trim**

5-1/2" Exposure
 16' Length (4877 mm)
 3/4" Channel Pocket
 Matte Texture
 Low-Gloss Finish

Packaging:
 10 pcs. per ctn.



Snow White

Almond

Chesapeake Gray

Dover Gray

Monterey Sand

Pebble

Storm

DESIGNER**COLOURS**

Coastal Blue†

Dark Drift†

Hudson Slate†

Iron Ore†

Majestic Brick†

Marine Dusk†

Meadow Fern†

Midnight Surf†

Moonlit Moss†

Rockport Brown†

Rockwell Blue†

Smoked Timber†


Windswept Smoke†

†Designer Colour; not
 available in British
 Columbia and Alberta.

PRODUCT CODE & DESCRIPTION

COLOURS

CP010
**3-1/2" ALIGN
Trim***



3-1/2" Exposure
16' Length (4877 mm)
3/4" Channel Pocket
Matte Texture
Low-Gloss Finish

Packaging:
10 pcs. per ctn.

Snow White

Dover Gray
Monterey Sand
Pebble
Storm

DESIGNER COLOURS

Rockport Brown*

*Designer Colour; not
available in British
Columbia and Alberta.

CP009
**5-1/2" ALIGN
Trim***




5-1/2" Exposure
16' Length (4877 mm)
3/4" Channel Pocket
Matte Texture
Low-Gloss Finish

Packaging:
10 pcs. per ctn.

PRODUCT CODE & DESCRIPTION

COLOURS

CP007
3-1/2" ALIGN
Outside Corner Post



3-1/2" Exposure
 12' Length (3658 mm)
 3/4" Channel Pocket
 Matte Texture
 Low-Gloss Finish

Packaging:
 10 pcs. per ctn.

Snow White
 Almond
 Chesapeake Gray
 Dover Gray
 Monterey Sand
 Pebble
 Storm

CP005
5-1/2" ALIGN
Outside Corner Post




5-1/2" Exposure
 12' Length (3658 mm)
 3/4" Channel Pocket
 Matte Texture
 Low-Gloss Finish

Packaging:
 10 pcs. per ctn.

DESIGNER COLOURS
 Coastal Blue†
 Dark Drift†
 Hudson Slate†
 Iron Ore†
 Majestic Brick†
 Marine Dusk†
 Meadow Fern†
 Midnight Surf†
 Moonlit Moss†
 Rockport Brown†
 Rockwell Blue†
 Smoked Timber†
 Windswept Smoke†

CP008
ALIGN
J-Channel



1" Face
 12' Length (3658 mm)
 3/4" Channel Pocket
 Matte Texture
 Low-Gloss Finish

Packaging:
 32 pcs. per ctn.

†Designer Colour; not available in British Columbia and Alberta.

CP011
ALIGN Finish Trim
(Utility Trim)



12'6" Length (3810 mm)

Packaging:
 20 pcs. per ctn.


Snow White

PRODUCT CODE & DESCRIPTION**COLOURS**

CP001

10' Length (3048 mm)

Universal

**2-1/2" ALIGN Steel
Starter Strip**Packaging:
24 pcs. per ctn.

5244R

Elongates Nail Slot

Nail Slot Punch

ALIGN Composite Cladding is compatible with a range of trim options including vinyl accessories 65504/65524, 65520/65521, 65533, 65538 on pages 20-22 and aluminum flatstock 3037 on page 46.

PRODUCT CODE & DESCRIPTION

COLOURS

65504/65524 (Dark Colours)

3-1/2"


Outside Corner Post

3-1/2" Face (88.9 mm)

10' Length (3048 mm)

Brushed Texture

See Matrix On
Pages 54-55.



Packaging:
10 pcs. per ctn.
100 lineal ft. per ctn. (30.5 m)

65501

3"


Outside Corner Post

3" Face (76.2 mm)

10' Length (3048 mm)

Brushed Texture

Packaging:
10 pcs. per ctn.
100 lineal ft. per ctn. (30.5 m)



65507

6" Designer


Outside Corner Post

6" Face (152.4 mm)

20' Length (6096 mm)

Brushed Texture

Packaging:
5 pcs. per ctn.
100 lineal ft. per ctn. (30.5 m)



68030

Bay and Bow


Outside Corner Post

2" Face (50.8 mm)

12'6" Length (3810 mm)

Matte Texture

Packaging:
10 pcs. per ctn.
125 lineal ft. per ctn. (38 m)



PRODUCT CODE & DESCRIPTION


COLOURS

68020

Beaded Corner Post with Foam Insert

20' Length (6096 mm)
Matte Texture

See Matrix On
Pages 54-55.



Packaging:
5 pcs. per ctn.
100 lineal ft. per ctn. (30.5 m)


65520/65521 (Dark Colours)

3-1/2"

3/4" Inside Corner Post

10' Length (3048 mm)
Brushed Texture

Packaging:
10 pcs. per ctn.
100 lineal ft. per ctn. (30.5 m)




65560

1/2" J-Channel

12' Length (3658 mm)
Brushed Texture

Packaging:
40 pcs. per ctn.
480 lineal ft. per ctn. (146.3 m)




65536

5/8" Premium J-Channel

12' Length (3658 mm)
Brushed Texture

Packaging:
40 pcs. per ctn.
480 lineal ft. per ctn. (146.3 m)



PRODUCT CODE & DESCRIPTION


COLOURS

65533
**3/4" Premium
 J-Channel**

12' Length (3658 mm)
 Brushed Texture

See Matrix On
 Pages 54-55.

Packaging:
 40 pcs. per ctn.
 480 lineal ft. per ctn. (146.3 m)




65606 (Special Order)
**1-1/4" J-Channel*
 with 1" Face**

12' Length (3658 mm)
 Brushed Texture

Packaging:
 30 pcs. per ctn.
 432 lineal ft. per ctn. (131.7 m)


*Can be used with Sequoia Select EnFusion
 insulated siding.



65538
**2-1/2" Wide Face
 J-Channel**

12' Length (3658 mm)
 Brushed Texture

Packaging:
 18 pcs. per ctn.
 216 lineal ft. per ctn. (65.8 m)




65570/65571
**Undersill Trim*
 (Utility Trim)**

12' Length (3658 mm)
 Brushed Texture


Packaging:
 40 pcs. per ctn.
 480 lineal ft. per ctn. (146.3 m)

*Also used as a starter strip for 5" lineal.




PRODUCT CODE & DESCRIPTION**COLOURS**


67750

**Double Undersill Trim
(Utility Trim)**12' Length (3658 mm)
Smooth TextureSee Matrix On
Pages 54-55.Packaging:
25 pcs. per ctn.
300 lineal ft. per ctn. (91.5 m)


65581

Drip Cap12' Length (3658 mm)
Brushed TexturePackaging:
45 pcs. per ctn.
540 lineal ft. per ctn. (164.6 m)

65583

**3-1/2\" Window/Door
Surround**3-1/2\" Face (88.9 mm)
20' Length (6096 mm)
Matte TexturePackaging:
5 pcs. per ctn.
100 lineal ft. per ctn. (30.5 m)

65750

**5\" Window/Door
Surround**5\" Face (127 mm)
20' Length (6096 mm)
Matte TexturePackaging:
10 pcs. per ctn.
200 lineal ft. per ctn. (61 m)

PRODUCT CODE & DESCRIPTION

COLOURS


65700

Surround Starter

12' Length (3658 mm)

See Matrix On
Pages 54-55.

Packaging:
25 pcs. per ctn.
300 lineal ft. per ctn. (91.4 m)




65551

Starter Strip*

12' Length (3658 mm)

Packaging:
40 pcs. per ctn.
480 lineal ft. per ctn. (146.3 m)

*For Sequoia Select, use Universal starter strip
(0109025) located on page 38.




65599

F-Channel

12' Length (3658 mm)

Brushed Texture

Packaging:
24 pcs. per ctn.
288 lineal ft. per ctn. (87.8 m)




68080

3/4\" F-Channel

12'6\" Length (3810 mm)

Brushed Texture

Packaging:
32 pcs. per ctn.
400 lineal ft. per ctn. (122 m)




PRODUCT CODE & DESCRIPTION**COLOURS**

65568
**3/8" Soffit Cove
J-Channel**

12'6" Length (3810 mm)
Matte Texture

See Matrix On
Pages 54-55.


Packaging:
24 pcs. per ctn.
300 lineal ft. per ctn. (91.5 m)



65548
Soffit Double Channel

12' Length (3658 mm)
Brushed Texture


Packaging:
20 pcs. per ctn.
240 lineal ft. per ctn. (73.2 m)



65590
Beltline Trim

12' Length (3658 mm)
Brushed Texture

Packaging:
30 pcs. per ctn.
360 lineal ft. per ctn. (109.7 m)
Ship. wt: 39 lb (18 kg)





DELUXE™

ALUMINUM SIDING

ALUMINUM SIDING

PRODUCT CODE & DESCRIPTION


COLOURS

1302

8" Horizontal

1/2" Butt (12.7 mm)
8" Exposure per Panel (203.2 mm)
12'6" Length (3810 mm)
Poly Finish
Smooth Texture

See Matrix On
Page 56.




Packaging:
24 pcs. per ctn.
2 sqs. per ctn. (18.58 m²)

1191

Double 4" Clapboard

1/2" Butt (12.7 mm)
2-4" Exposure per Panel (101.6/203.2 mm)
12'6" Length (3810 mm)
Poly Finish
Smooth Texture

Packaging:
24 pcs. per ctn.
2 sqs. per ctn. (18.58 m²)




1302

8" Vertical Board & Batten

8" Exposure per Panel (203.2 mm)
10' Length (3048 mm)
Poly Finish
Smooth Texture

Packaging:
15 pcs. per ctn.
1 sq. per ctn. (9.29 m²)




1438

Vertical "V" Standard Gauge (0.40 mm)

7-1/4" Exposure per Panel (184.2 mm)
9'7-3/8" Length (2930 mm)
Poly Finish
Smooth Texture


Packaging:
17 pcs. per ctn.
1 sq. per ctn. (9.29 m²)



26

PRODUCT CODE & DESCRIPTION**COLOURS**

1429

**Vertical "V"
Heavy Gauge
(0.44 mm)**7-1/4" Exposure per Panel
(184.2 mm)
12' Length (3658 mm)
Poly Finish
Smooth TextureSee Matrix On
Page 56.Packaging:
17 pcs. per ctn.
1 sq. per ctn. (9.29 m²)



WOODGRAIN™ 2000 | ALUMINUM SIDING

ALUMINUM SIDING

PRODUCT CODE & DESCRIPTION


COLOURS

1003

8" Horizontal

1/2" Butt (12.7 mm)
8" Exposure per Panel (203.2 mm)
12'6" Length (3810 mm)
Woodgrain Texture

See Matrix on
Page 56.




Packaging:
24 pcs. per ctn.
2 sqs. per ctn. (18.58 m²)

1192

**Double 4" Clapboard
Standard Gauge
(0.40 mm)**

1/2" Butt (12.7 mm)
2-4" Exposure per Panel
(101.6/203.2 mm)
12'6" Length (3810 mm)
Woodgrain Texture

Packaging:
24 pcs. per ctn.
2 sqs. per ctn. (18.58 m²)




1186

**Double 4" Clapboard
Heavy Gauge
(0.44 mm)**

1/2" Butt (12.7 mm)
2-4" Exposure per Panel
(101.6/203.2 mm)
12'6" Length (3810 mm)
Woodgrain Texture

Packaging:
24 pcs. per ctn.
2 sqs. per ctn. (18.58 m²)




1188

**Double 4" Dutch Lap
Standard Gauge
(0.40 mm)**

1/2" Butt (12.7 mm)
2-4" Exposure per Panel
(101.6/203.2 mm)
12'6" Length (3810 mm)
Woodgrain Texture

Packaging:
24 pcs. per ctn.
2 sqs. per ctn. (18.58 m²)




PRODUCT CODE & DESCRIPTION**COLOURS**

1185

**Double 4" Dutch Lap
Heavy Gauge
(0.44 mm)**

1/2" Butt (12.7 mm)
2-4" Exposure per Panel
(101.6/203.2 mm)
12'6" Length (3810 mm)
Woodgrain Texture

See Matrix on
Page 56.




Packaging:
24 pcs. per ctn.
2 sqs. per ctn. (18.58 m²)

1303

**8" Vertical
Board & Batten**

1/2" Butt (12.7 mm)
8" Exposure per Panel (203.2 mm)
10' Length (3048 mm)
Woodgrain Texture

Packaging:
15 pcs. per ctn.
1 sq. per ctn. (9.29 m²)




1439

**Vertical "V"
Standard Gauge
(0.40 mm)**

7-1/4" Exposure per Panel (184.2 mm)
9'7-3/8" Length (2930 mm)
Woodgrain Texture

Packaging:
17 pcs. per ctn.
1 sq. per ctn. (9.29 m²)




1425

**Vertical "V"
Heavy Gauge
(0.44 mm)**

7-1/4" Exposure per Panel (184.2 mm)
9'7-3/8" Length (2930 mm)
Woodgrain Texture

Packaging:
17 pcs. per ctn.
1 sq. per ctn. (9.29 m²)




PRODUCT CODE & DESCRIPTION

COLOURS

1603
16" 2-Panel Soffit
Vented
Standard Gauge

16" Exposure per Panel (406.4 mm)
12'1-5/16" Length (3691 mm)
4.02 sq. in. ventilation per lineal ft.
Smooth Texture


See Matrix On
Pages 58-59.



Packaging:
18 pcs. per ctn.
3 sqs. per ctn. (27.62 m²)

1620
16" 2-Panel Soffit
Solid
Heavy Gauge


16" Exposure per Panel (406.4)
12'1-5/16" Length (3691 mm)
Smooth Texture



Packaging:
12 pcs. per ctn.
2 sqs. per ctn. (18.58 m²)

1622
16" 2-Panel Soffit
Vented
Heavy Gauge

16" Exposure per Panel (406.4 mm)
12'1-15/16" Length (3708 mm)
4.02 sq. in. ventilation per lineal ft.
Smooth Texture



Packaging:
12 pcs. per ctn.
2 sqs. per ctn. (18.58 m²)

PRODUCT CODE & DESCRIPTION


COLOURS

1601
**16" 4-Panel Soffit
Solid**

16" Exposure per Panel (406.4 mm)
12'2-3/8" Length (3718 mm)
Smooth Texture

See Matrix On
Pages 58-59.


Packaging:
18 pcs. per ctn.
3 sqs. per ctn. (27.62 m²)



1606
**16" 4-Panel Soffit
Vented**

16" Exposure per Panel (406.4 mm)
12'2-3/8" Length (3718 mm)
4.12 sq. in. ventilation per lineal ft.
Smooth Texture


Packaging:
18 pcs. per ctn.
3 sqs. per ctn. (27.62 m²)



1615
**16" 4-Panel Soffit
Vented
Heavy Gauge**

16" Exposure per Panel (406.4 mm)
12'2-3/8" Length (3718 mm)
4.12 sq. in. ventilation per lineal ft.
Smooth Texture

Packaging:
18 pcs. per ctn.
3 sqs. per ctn. (27.62 m²)



PRODUCT CODE & DESCRIPTION


COLOURS

2330
18" 3-Panel Soffit
Solid
Heavy Gauge

18" Exposure per Panel (457.2 mm)
10' Length (3048 mm)
Smooth Texture

See Matrix On
Pages 58-59.


Packaging:
12 pcs. per ctn.
1.92 sqs. per ctn. (17.8 m²)



2345
18" 3-Panel Soffit
Vented
Heavy Gauge

18" Exposure per Panel (457.2 mm)
10' Length (3048 mm)
5.46 sq. in. ventilation per lineal ft.
Smooth Texture

Packaging:
12 pcs. per ctn.
1.92 sqs. per ctn. (17.8 m²)



PRODUCT CODE & DESCRIPTION


COLOURS

1694
**4" Fascia
Standard Gauge**

9'10" Length (3000 mm)
Ribbed

See Matrix On
Pages 58-59.


Packaging:
30 pcs. per ctn.
295 lineal ft. per ctn. (90 m)



1693
**4" Fascia
Economy Gauge**

9'10" Length (3000 mm)
Ribbed


Packaging:
30 pcs. per ctn.
295 lineal ft. per ctn. (90 m)



1696/1697
**6" Fascia
Standard Gauge**

9'10" Length (3000 mm)
Ribbed


Packaging:
20 pcs. per ctn.
197 lineal ft. per ctn. (60 m)



1691
**6" Fascia
Economy Gauge**

9'10" Length (3000 mm)
Ribbed

Packaging:
20 pcs. per ctn.
197 lineal ft. per ctn. (60 m)




PRODUCT CODE & DESCRIPTION

COLOURS

2020
6" Fascia
Heavy Gauge

6"
(152.4)



9'10" Length (3000 mm)
Ribbed

See Matrix On
Pages 58-59.

Packaging:
20 pcs. per ctn.
197 lineal ft. per ctn. (60 m)

1697 available in AluCopper.

2024
6" Fascia
Heavy Gauge

6"
(152.4)




9'10" Length (3000 mm)
Plain

Packaging:
25 pcs. per ctn.
245.8 lineal ft. per ctn. (75 m)

1698
8" Fascia
Standard Gauge

8"
(203.2)




9'10" Length (3000 mm)
Ribbed

Packaging:
20 pcs. per ctn.
197 lineal ft. per ctn. (60 m)

2030
8" Fascia
Heavy Gauge

8"
(203.2)




9'10" Length (3000 mm)
Ribbed


Packaging:
20 pcs. per ctn.
197 lineal ft. per ctn. (60 m)

PRODUCT CODE & DESCRIPTION**COLOURS**

2025

**8" Fascia
Heavy Gauge**8"
(203.2)9'10" Length (3000 mm)
PlainPackaging:
25 pcs. per ctn.
245.8 lineal ft. per ctn. (75 m)See Matrix On
Pages 58-59.

1670


**10" Fascia
Standard Gauge**10"
(254)9'10" Length (3000 mm)
RibbedPackaging:
20 pcs. per ctn.
197 lineal ft. per ctn. (60 m)

PRODUCT CODE & DESCRIPTION**COLOURS**

2319
Outside Corner Post

2-1/2" Face (63.5 mm)
10' Length (3048 mm)
Smooth Texture


See Matrix On
Pages 60-63.



Packaging:
10 pcs. per ctn.

2312
Outside Corner Post


2-1/2" Face (63.5 mm)
10' Length (3048 mm)
Woodgrain Texture



Packaging:
10 pcs. per ctn.

2300
Individual Corner Cap


8" Exposure (203.2 mm)
Smooth Texture



Packaging:
100 pcs. per ctn.

2502
3/4" J Trim

12' Length (3658 mm)
Smooth Texture



Packaging:
40 pcs. per ctn.

PRODUCT CODE & DESCRIPTION

COLOURS


2503

Universal J

10' Length (3048 mm)
Smooth Texture

See Matrix On
Pages 60-63.

Packaging:
20 pcs. per ctn.




2520/2522

Soffit J (BSP)*

12' Length (3658 mm)
Smooth Texture

Packaging:
25 pcs. per ctn.

2522 – only available in AluCopper




2507

3/4" Wideface Soffit J

12' Length (3658 mm)
Smooth Texture

Packaging:
24 pcs. per ctn.




1692

1/2" Soffit J

12' Length (3658 mm)
Smooth Texture


Packaging:
25 pcs. per ctn.




*BSP – both sides painted.

PRODUCT CODE & DESCRIPTION**COLOURS**


2538

L-Trim Small12' Length (3658 mm)
Smooth TextureSee Matrix On
Pages 60-63.Packaging:
25 pcs. per ctn.


2543

Drip Cap12' Length (3658 mm)
Smooth TexturePackaging:
20 pcs. per ctn.

2567

Roof Edge Drip Cap10' Length (3048 mm)
Smooth TexturePackaging:
20 pcs. per ctn.

2573

3" 0° Roof Edge9'10" Length (3000 mm)
Smooth TexturePackaging:
20 pcs. per ctn.


PRODUCT CODE & DESCRIPTION**COLOURS**

2575
4" 0° Roof Edge

9'10" Length (3000 mm)
Smooth Texture

See Matrix On
Pages 60-63.


Packaging:
20 pcs. per ctn.



2577
6" 0° Roof Edge

9'10" Length (3000 mm)
Smooth Texture


Packaging:
20 pcs. per ctn.



2550
**Snap-Lock
Sill Trim**

12' Length (3658 mm)
Smooth Texture


Packaging:
40 pcs. per ctn.



0109025
Universal Starter Strip

10' Length (3100 mm)
Smooth Texture

Packaging:
50 pcs. per ctn.




PRODUCT CODE & DESCRIPTION**COLOURS**

2504
Undersill Trim

10' Length (3048 mm)
Smooth Texture

See Matrix On
Pages 60-63.


Packaging:
25 pcs. per ctn.



2043
Fascia Trim

10' Length (3048 mm)
Smooth Texture


Packaging:
20 pcs. per ctn.



2311
**Woodgrain™ 2000
Individual Corner Cap**

8" Exposure (203.2 mm)
Woodgrain Texture

Packaging:
100 pcs. per ctn.




PRODUCT CODE & DESCRIPTION

COLOURS

1750

Double 4" Clapboard



1/2" Butt (12.7 mm)
2-4" Exposure per Panel
(101.6/203.2 mm)
12'6" Length (3810 mm)
Kynar Finish
Roughsawn Texture


Packaging:
10 pcs. per ctn.
1 sq. per ctn. (9.29 m²)

Bright White

Chelsea Bluff
Delray Sand
Dover Gray
Iron Ore
Juniper Grove
Monterey Sand
Rockwell Blue
Sable
Storm
Taylor Red
Thistle
Watermill Blue

1755

Double 5" Clapboard




1/2" Butt (12.7 mm)
2-5" Exposure per Panel
(127/254 mm)
12' 6" Length (3810 mm)
Kynar Finish
Roughsawn Texture

Packaging:
10 pcs. per ctn.
1 sq. per ctn. (9.29 m²)

1748

8" Horizontal




1/2" Butt (12.7 mm)
8" Exposure per Panel (203.2 mm)
12'6" Length (3810 mm)
Kynar Finish
Roughsawn Texture

Packaging:
12 pcs. per ctn.
1 sq. per ctn. (9.29 m²)

1752

12" Vertical Board & Batten



5/8" Batten Height (15.9 mm)
2" Batten Width (50.8 mm)
12" Exposure per Panel (304.8 mm)
10' Length (3048 mm)
Kynar Finish
Medium Woodgrain Texture

Packaging:
10 pcs. per ctn.
1 sq. per ctn. (9.29 m²)


PRODUCT CODE & DESCRIPTION

COLOURS

1754
**Double 5"
 Clapboard**

1/2" Butt (12.7 mm)
 2-5" Exposure per Panel
 (127/254 mm)
 12' Length (3658 mm)
 PVC Finish
 Woodgrain Texture

Packaging:
 10 pcs. per ctn.
 1 sq. per ctn. (9.29 m²)




Bright White

Almond
 Brownstone
 Canyon Clay
 Dover Gray
 Norwood
 Pacific Blue
 Sable
 Sage
 Thistle
 Wicker

1751
8" Horizontal

1/2" Butt (12.7 mm)
 8" Exposure per Panel (203.2 mm)
 12'6" Length (3810 mm)
 PVC Finish
 Woodgrain Texture

Packaging:
 12 pcs. per ctn.
 1 sq. per ctn. (9.29 m²)




PRODUCT CODE & DESCRIPTION**COLOURS**

1813
**3/4" Outside
Corner Post**

2-1/2" Face (63.5 mm)
10' Length (3048 mm)
PVC Striated Finish
Woodgrain Texture

See Matrix On
Page 57.




Packaging:
10 pcs. per ctn.
100 lineal ft. per ctn. (30.5 m)

1814
3/4" J-Channel

12'6" Length (3810 mm)
PVC Striated Finish
Smooth Texture


Packaging:
24 pcs. per ctn.
300 lineal ft. per ctn. (91.5 m)



1829
2-1/2" Starter Strip

10' Length (3048 mm)


Packaging:
26 pcs. per ctn.
260 lineal ft. per ctn. (79.3 m)



1835
**Universal
3/4" Outside
Corner Post
Kynar**

2-1/2" Face (63.5 mm)
10' Length (3048 mm)
Kynar PVDF Finish
Woodgrain Texture

Packaging:
10 pcs. per ctn.
100 lineal ft. per ctn. (30.5 m)




PRODUCT CODE & DESCRIPTION

COLOURS

1842
3/4" J-Channel
 Kynar

12'6" Length (3810 mm)
 Kynar PVDF Finish
 Woodgrain Texture


See Matrix On
 Page 57.



Packaging:
 24 pcs. per ctn.
 300 lineal ft. per ctn. (91.5 m)

1841
1-1/8" J-Channel
 Kynar

12'6" Length (3810 mm)
 Kynar PVDF Finish
 Woodgrain Texture




Packaging:
 24 pcs. per ctn.
 300 lineal ft. per ctn. (91.5 m)

1850
Snap-Lock
Finish Trim
 Kynar

12'6" Length (3810 mm)
 Kynar PVDF Finish
 Woodgrain Texture

Packaging:
 24 pcs. per ctn.
 300 lineal ft. per ctn. (91.5 m)



PRODUCT CODE & DESCRIPTION

COLOURS

1877/29-GA
Flatstock
PVC Coated

20-7/8" Width (530.23 mm)
50' Length (15.24 m)

See Matrix On
Page 57.




FLATSTOCK | ALUMINUM

PRODUCT CODE & DESCRIPTION

COLOURS

3059 98.5' Length (30 m)
**Performance G8
Flatstock
24" x 98.5' (BSP)***

See Matrix On
Pages 60-61.




3041 98.5' Length (30 m)
**Performance G8
Flatstock
24" x 98.5' (OSP)***




3036 50' Length (15.24 m)
**Flatstock
24" x 50' (BSP)***

NOTE: Colour over Bright White, Light Gauge.
Reverse side is Bright White.



3037 98.5' Length (30 m)
**Flatstock
24" x 98.5' (BSP)***

NOTE: Colour over Bright White, Light Gauge.
Reverse side is Bright White.



46


*BSP – both sides painted.
*OSP – one side painted.

PRODUCT CODE & DESCRIPTION**COLOURS**

3307

**Flatstock
24" x 98.5' (BSP)*
CanExel Colours**

98.5' Length (30 m)

NOTE: Colour over Bright White, Light Gauge.
Reverse side is Bright White.See Matrix On
Pages 60-61.

3309

**Flatstock
24" x 98.5' (OSP)***

98.5' Length (30 m)



3304

**Flatstock
24" x 50' (BSP)***


50' Length (15.24 m)

NOTE: Colour over Bright White, Light Gauge.
Reverse side is Bright White.

3531

**Flatstock
24" x 98.5' (BSP)***

98.5' Length (30 m)

NOTE: Colour over Bright White, Light Gauge.
Reverse side is Bright White.

GUTTER COIL | ALUMINUM

PRODUCT CODE & DESCRIPTION

COLOURS

3025

**10-1/2" Gutter Coil
(OSP)***

Width per coil 10-1/2" (267 mm)

See Matrix On
Pages 60-61.



3006

**11-7/8" Gutter Coil
(OSP)***

Width per coil 11-7/8" (301.5 mm)



3009

**11-7/8" Gutter Coil
(BSP)***

Width per coil 11-7/8" (301.5 mm)
White Exterior



3045

**11-7/8" Gutter Coil
Heavy Gauge
(OSP)***

Width per coil 11-7/8" (301.5 mm)
Thickness: 0.66 mm



48

*BSP – both sides painted.
*OSP – one side painted.

PRODUCT CODE & DESCRIPTION**COLOURS**

3049

**11-7/8" Gutter Coil
Heavy Gauge
(BSP)***

Width per coil 11-7/8" (301.5 mm)

White Exterior

Thickness: 0.027 mm

See Matrix On
Pages 60-61.

3012

**13-1/2" Gutter Coil
(BSP)***

Width per coil 13-1/2" (343 mm)



3084

**6" Gutter Coil
(BSP)***

Width per coil 6" (152.4 mm)



ALIGN CLADDING AND ACCESSORIES COLOUR MATRIX

- Available in this colour.

	Colour Palette										
	01 Snow White	632 Almond	872 Chesapeake Gray	625 Coastal Blue	655 Dark Drift	127 Dover Gray	873 Hudson Slate	642 Iron Ore	876 Majestic Brick	877 Marine Dusk	874 Meadow Fern
ALIGN Cladding											
7" Plank	•	•	•	•	•	•	•	•	•	•	•
12" Board & Batten	•	•	•	•	•	•	•	•	•	•	•
ALIGN Accessories											
CP003 5-1/2" H-Trim	•	•	•	•	•	•	•	•	•	•	•
CP010 3-1/2" Trim	•					•					
CP009 5-1/2" Trim	•					•					
CP007 3-1/2" Outside Corner Post	•	•	•	•	•	•	•	•	•	•	•
CP005 5-1/2" Outside Corner Post	•	•	•	•	•	•	•	•	•	•	•
CP008 J-Channel	•	•	•	•	•	•	•	•	•	•	•
CP011 Finish Trim											
CP001 2-1/2" Steel Starter Strip											
5244R Nail Slot Punch											

VINYL SIDING AND SOFFIT COLOUR MATRIX

• Available in this colour.

	Classic Colours											
	001 Snow White	632 Almond	616 Amber	010 Canyon Clay	872 Chesapeake Gray	127 Dover Gray	633 Juniper Grove	012 Linen	002 Maize	673 Monterey Sand	006 Pearl	628 Pebble
Sequoia Select												
Double 4" Clapboard	•	•		•	•	•	•	•	•	•	•	•
Double 4-1/2" Dutch Lap	•	•		•	•	•	•	•	•	•	•	•
Double 5" Clapboard*	•	•		•	•	•	•	•	•	•	•	•
Double 5" Dutch Lap*	•	•		•	•	•	•	•	•	•	•	•
Board & Batten												
7" Vertical Board & Batten*	•	•		•	•	•	•	•	•	•	•	•
Fair Oaks												
Double 4" Clapboard	•	•		•	•	•	•	•	•	•	•	•
Double 4" Dutch Lap	•	•		•	•	•	•	•	•	•	•	•
Double 5" Clapboard*	•	•		•	•	•	•	•	•	•	•	•
Double 5" Dutch Lap*	•	•		•	•	•	•	•	•	•	•	•
Concord												
Double 4" Clapboard	•	•		•	•	•	•	•	•	•	•	•
Double 4" Dutch Lap	•	•		•	•	•	•	•	•	•	•	•
Double 5" Clapboard	•	•		•	•	•	•	•	•	•	•	•
Double 5" Dutch Lap	•	•		•	•	•	•	•	•	•	•	•
10" Vertical	•	•		•	•	•	•	•	•	•	•	•
Driftwood II												
Double 4" Clapboard	•	•	•	•	•	•	•	•	•	•	•	•
Double 4-1/2" Dutch Lap	•	•	•	•	•	•	•	•	•	•	•	•
Vinyl Soffit												
Oxford Premium 10"	•	•		•	•	•	•	•	•	•	•	•
Beaded Premium 8"	•			•				•		•		•
Fairweather 12"	•	•		•	•	•	•	•	•	•	•	•
EZ Lock 8"	•							•				

Note: Black and Musket Brown are for soffit use only, not as vertical siding. Beaded Premium soffit is not offered as vertical siding.

*Designer Colours not available in British Columbia and Alberta.

VINYL ACCESSORIES | COLOUR MATRIX

- Available in this colour.

	Classic Colours											
	001 Snow White	632 Almond	616 Amber	010 Canyon Clay	872 Chesapeake Gray	127 Dover Gray	633 Juniper Grove	012 Linen	002 Maize	673 Monterey Sand	006 Pearl	628 Pebble
65504 3-1/2" Outside Corner Post (OCP)	•	•		•	•	•	•	•	•	•	•	•
65524 3-1/2" OCP – Dark Colours												
65501 3" Outside Corner Post	•	•	•	•	•	•	•	•	•	•	•	•
65507 6" Designer Outside Corner Post	•	•		•		•	•			•	•	•
65520 Inside Corner Post	•	•	•	•	•	•	•	•	•	•	•	•
65521 Inside Corner Post – Dark Colours												
65560 1/2" J-Channel	•	•		•	•	•	•	•	•	•	•	•
65536 5/8" Premium J-Channel	•	•	•	•	•	•	•	•	•	•	•	•
65533 3/4" Premium J-Channel	•	•		•	•	•	•	•	•	•	•	•
65606 1-1/4" J-Channel	•	•		•		•	•	•	•	•	•	•
65538 2-1/2" Wide Face J-Channel	•											
65570 Undersill Trim	•	•	•	•	•	•	•	•	•	•	•	•
65571 Undersill Trim – Dark Colours												
67750 Double Undersill Trim	•	•	•	•		•	•	•	•	•	•	•
65581 Drip Cap	•	•	•	•	•	•	•	•	•	•	•	•
65700 Surround Starter	•											
65551 Starter Strip												
65599 F-Channel	•	•	•	•	•	•	•	•	•	•	•	•
68080 3/4" F-Channel	•											•
65568 3/8" Soffit Cove J-Channel	•											
65548 Soffit Double Channel	•											
65590 Beltline Trim	•				•							•
68030 Bay and Bow Outside Corner Post	•											
68020 Beaded Corner Post w/insulation	•											
65583 3-1/2" Window/Door Surround	•	•						•				
65750 5" Window/Door Surround	•											

Note: Black and Musket Brown vinyl accessories are for soffit use only.

ALUMINUM SIDING COLOUR MATRIX

- Available in this colour.

		Deluxe Aluminum				Woodgrain 2000				
		8" Horizontal	Double 4" Clapboard	8" Vertical Board & Batten	Vertical "V"	8" Horizontal	Double 4" Clapboard	Double 4" Dutch Lap	8" Vertical Board & Batten	7-1/4" Vertical "V"
Colour Palette	431 Bright White	•	•	•	•	•	•	•	•	•
	429 Ice White				•					•
	432 Almond		•	•	•		•	•	•	•
	425 Black				•					•
	471 Brownstone		•		•					•
	410 Canyon Clay		•		•		•			•
	4C1 Chesapeake Gray		•		•			•		•
	454 Chestnut Brown		•	•	•		•	•	•	•
	462 Commercial Brown		•	•	•		•	•	•	•
	457 Dark Drift							•		
	436 Dover Gray		•		•		•			•
	4C2 Hudson Slate		•		•			•		•
	4P6 Iron Ore		•		•			•		•
	402 Maize		•	•	•		•	•	•	•
	459 Pebble		•	•	•		•	•	•	•
	447 Sable									•
	440 Sandstone				•					•
	423 Slate		•		•		•			•
	470 Storm		•		•		•	•		•
	407 Tan		•		•		•			•
438 Wicker		•		•		•			•	
406 Windswept Smoke		•		•			•		•	
Variegated	990 Aspen Gray									
	992 Chestnut Brown									
	994 Maple Tan									
	996 Tawny Oak									

Additional colours available. Not all colours available in all profiles; see your Gentek representative for details.

Note: Colours for standard gauge and heavy gauge panels may vary. Confirm colour availability with your Gentek representative by specific product code.

STEEL SIDING COLOUR MATRIX

	Colour Palette												
	431 Bright White	796 Chelsea Bluff	795 Delray Sand	836 Dover Gray	4P6 Iron Ore	633 Juniper Grove	673 Monterey Sand	637 Rockwell Blue	712 Sable	470 Storm	793 Taylor Red	826 Thistle	714 Watermill Blue
Sierra Steel with Kynar													
Double 4" Clapboard	•	•	•	•	•	•	•	•	•	•	•	•	•
Double 5" Clapboard	•	•	•	•	•	•	•	•	•	•	•	•	•
Horizontal 8"	•	•	•	•	•	•	•	•	•	•	•	•	•
12" Vertical Board & Batten	•	•	•	•	•	•	•	•	•	•	•	•	•
Steel Accessories													
1835 3/4" Outside Corner Post – Kynar	•	•	•	•	•	•	•	•	•	•	•	•	•
1842 3/4" J-Channel – Kynar	•	•	•	•	•	•	•	•	•	•	•	•	•
1841 1-1/8" J-Channel – Kynar	•	•	•	•	•	•	•	•	•	•	•	•	•
1850 Snap-Lock Finish – Kynar	•	•	•	•	•	•	•	•	•	•	•	•	•
1715 24" x 50" Alum. Trim Coil – Poly	•	•	•	•	•	•	•	•	•	•	•	•	•

	Colour Palette											
	831 Bright White	832 Almond	871 Brownstone	810 Canyon Clay	836 Dover Gray	866 Norwood	201 Pacific Blue	712 Sable	817 Sage	826 Thistle	838 Wicker	Neutral
SteelSide												
Double 5" Clapboard	•	•	•	•	•	•	•	•	•	•	•	
Horizontal 8"	•	•	•	•	•	•	•	•	•	•	•	
Steel Accessories												
1813 3/4" Outside Corner Post	•	•	•	•	•	•	•	•	•	•	•	
1814 3/4" J-Channel	•	•	•	•	•	•	•	•	•	•	•	
1829 2-1/2" Starter Strip												•

	431 Bright White	826 Thistle
Steel Flatstock		
1877/29-GA 20-7/8" x 50' (PVC)	•	•

ALUMINUM SOFFIT AND FASCIA COLOUR MATRIX

• Available in this colour.

Colour Palette	Aluminum Soffit					Aluminum Fascia									
	16" 2-Panel Standard Gauge	16" 2-Panel Heavy Gauge	16" 4-Panel Standard Gauge	16" 4-Panel Heavy Gauge	18" 3-Panel Heavy Gauge	4" Standard Gauge, Ribbed	4" Economy Gauge, Ribbed	6" Standard Gauge, Ribbed	6" Economy Gauge, Ribbed	6" Heavy Gauge, Ribbed	6" Heavy Gauge, Plain	8" Standard Gauge, Ribbed	8" Heavy Gauge, Ribbed	8" Heavy Gauge, Plain	10" Standard Gauge, Ribbed
431 Bright White	•		•	•	•	•	•	•	•	•	•	•	•	•	•
429 Ice White	•		•					•				•			
430 Rainware White										•	•			•	
86 White 701			•	•										•	
432 Almond	•		•		•			•		•	•	•	•	•	•
475 AluCopper		•						•							
165 Antique Brown	•		•					•				•			•
425 Black	•		•	•				•				•			•
471 Brownstone	•		•					•				•			
467 Burgundy	•		•					•				•			•
410 Canyon Clay	•		•					•		•	•	•	•	•	•
414 Cashmere	•		•					•		•	•	•	•	•	•
4C1 Chesapeake Gray	•		•					•				•			•
454 Chestnut Brown	•		•		•		•		•	•	•	•	•	•	•
462 Commercial Brown	•		•	•				•		•	•	•	•	•	•
436 Dover Gray	•		•					•		•	•	•	•	•	•
4P5 Graphite	•		•					•				•			•
422 Ivy Green	•		•					•				•			•
402 Maize	•		•					•		•	•	•	•	•	•
4P4 Metallic Gray	•		•					•				•			•
4P8 Monterey Sand	•		•					•				•			•
468 Nutmeg	•		•		•		•		•			•			•
442 Old World Blue	•		•					•				•			•
434 Pearl			•												
459 Pebble	•		•					•		•	•	•	•	•	•
447 Sable	•		•					•				•			•
417 Sage	•		•					•				•			•
440 Sandstone	•		•					•		•	•	•	•	•	•
423 Slate	•		•	•				•				•			•
470 Storm	•		•					•				•			•
407 Tan	•		•					•				•			•
435 Wedgewood Blue	•		•					•				•			•
438 Wicker	•		•					•		•	•	•	•	•	•

Designer Colours	Aluminum Soffit					Aluminum Fascia										
		16" 2-Panel Standard Gauge	16" 2-Panel Heavy Gauge	16" 4-Panel Standard Gauge	16" 4-Panel Heavy Gauge	18" 3-Panel Heavy Gauge	4" Standard Gauge, Ribbed	4" Economy Gauge, Ribbed	6" Standard Gauge, Ribbed	6" Economy Gauge, Ribbed	6" Heavy Gauge, Ribbed	6" Heavy Gauge, Plain	8" Standard Gauge, Ribbed	8" Heavy Gauge, Ribbed	8" Heavy Gauge, Plain	10" Standard Gauge, Ribbed
	4P9 Coastal Blue	•	•	•					•				•			•
	457 Dark Drift	•	•	•					•				•			•
	4P3 Espresso	•	•	•					•				•			•
	4C2 Hudson Slate	•	•	•					•				•			•
4P6 Iron Ore	•	•	•	•				•				•			•	
4C5 Majestic Brick	•	•	•					•				•			•	
4C6 Marine Dusk	•	•	•					•				•			•	
4C3 Meadow Fern	•	•	•					•				•			•	
409 Midnight Surf	•	•	•					•				•			•	
413 Moonlit Moss	•	•	•					•				•			•	
4C4 Rockport Brown	•	•	•					•				•			•	
4P2 Rockwell Blue	•	•	•					•				•			•	
4C7 Smoked Timber	•	•	•					•				•			•	
406 Windswept Smoke	•	•	•					•				•			•	

Some colours are special order; see your Gentek representative for details.

ALUMINUM ACCESSORIES COLOUR MATRIX

- Available in this colour.

	Colour Palette											
	431 Bright White	429 Ice White	430 Rainware White	B01 White	432 Almond	475 AluCopper	165 Antique Brown	425 Black	B25 Black	322 Bright Red	471 Brownstone	467 Burgundy
2550 Snap-Lock Sill Trim	•				•							
0109025 Universal Starter Strip												
2502 3/4" J-Trim	•	•			•		•	•			•	•
2312 Outside Corner Post (Woodgrain)	•	•			•		•	•			•	•
2319 Outside Corner Post (Smooth)	•	•			•		•	•			•	•
2503 Universal J	•	•			•		•	•			•	•
2538 L-Trim Small	•	•			•		•	•			•	•
2543 Drip Cap	•	•			•		•	•			•	•
2504 Undersill Trim	•	•			•		•	•			•	•
2567 Roof Edge Drip Cap	•	•			•		•	•			•	•
2573 Roof Edge 3" 0 Degree 9'10"	•						•					
2575 Roof Edge 4" 0 Degree 9'10"	•						•					
2577 Roof Edge 6" 0 Degree 9'10"	•						•					
2043 Fascia Trim (BSP)	•	•			•		•	•			•	•
2300 Individual Corner Cap	•											
2311 Individual Corner Cap Woodgrain	•											
2520 Soffit J (BSP)	•	•			•		•	•			•	•
2507 3/4" Wideface Soffit J	•											
2522 Soffit J (OSP)						•						
1692 1/2" Soffit J	•	•			•		•	•			•	•
1690 Channel Runner						•						
Aluminum Flatstock												
3059 24" x 98.5' (BSP) Performance G8									•			
3041 24" x 98.5' (OSP) Performance G8		•										
3036 24" x 50' (BSP) Heavy Gauge	•				•		•	•			•	•
3037 24" x 98.5' (BSP)	•				•		•	•			•	•
3039 24" x 98.5' (OSP)	•	•	•									
3304 24" x 50' (BSP)	•				•		•					
3531 24" x 98.5' (BSP)	•				•		•	•				
Aluminum Gutter Coil												
3025 Downpipe Coil 10-1/2" (OSP)		•	•		•		•	•		•	•	•
3006 Gutter Coil 11-7/8" (OSP)			•									
3009 Gutter Coil 11-7/8" (BSP)					•		•	•		•	•	•
3045 Gutter Coil 11-7/8" (OSP) Heavy Gauge			•				•					
3049 Gutter Coil 11-7/8" (BSP) Heavy Gauge					•		•	•		•	•	
3012 Gutter Coil 13-1/2" (BSP)					•		•					
3084 Gutter Coil 6" (BSP)					•		•					

ALUMINUM ACCESSORIES COLOUR MATRIX

- Available in this colour.

	Designer Colours											
	4P9 Coastal Blue	457 Dark Drift	4P3 Espresso	4C2 Hudson Slate	4P6 Iron Ore	4C5 Majestic Brick	4C6 Marine Dusk	4C3 Meadow Fern	409 Midnight Surf	413 Moonlit Moss	4C4 Rockport Brown	4P2 Rockwell Blue
2550 Snap-Lock Sill Trim												
0109025 Universal Starter Strip												
2502 3/4" J-Trim	•	•	•	•	•	•	•	•	•	•	•	•
2312 3/4" Outside Corner Post (Woodgrain)	•	•	•	•	•	•	•	•	•	•	•	•
2319 3/4" Outside Corner Post (Smooth)	•	•	•	•	•	•	•	•	•	•	•	•
2503 Universal J	•	•	•	•	•	•	•	•	•	•	•	•
2538 L-Trim Small	•	•	•	•	•	•	•	•	•	•	•	•
2543 Drip Cap	•	•	•	•	•	•	•	•	•	•	•	•
2504 Undersill Trim	•	•	•	•	•	•	•	•	•	•	•	•
2567 Roof Edge Drip Cap	•	•	•	•	•	•	•	•	•	•	•	•
2573 Roof Edge 3" 0 Degree 9'10"												
2575 Roof Edge 4" 0 Degree 9'10"												
2577 Roof Edge 6" 0 Degree 9'10"												
2043 Fascia Trim (BSP)	•	•	•	•	•	•	•	•	•	•	•	•
2300 Individual Corner Cap												
2311 Individual Corner Cap Woodgrain												
2520 Soffit J (BSP)	•	•	•	•	•	•	•	•	•	•	•	•
2507 3/4" Wideface Soffit J												
2522 Soffit (OSP)												
1692 1/2" Soffit J	•	•	•	•	•	•	•	•	•	•	•	•
1690 Channel Runner												
Aluminum Flatstock												
3059 24" x 98.5' (BSP) Performance G8					•							
3041 24" x 98.5' (OSP) Performance G8												
3036 24" x 50' (BSP) Heavy Gauge	•	•	•	•	•	•	•	•	•	•	•	•
3037 24" x 98' 1/2" (BSP)	•	•	•	•	•	•	•	•	•	•	•	•
3039 24" x 98' 1/2" (OSP)												
3304 24" x 50' (BSP)												
3531 24" x 98' 1/2" (BSP)				•	•	•	•			•		
Aluminum Gutter Coil												
3025 Downpipe Coil 10-1/2" (OSP)	•	•	•	•	•	•	•	•	•	•	•	•
3006 Gutter Coil 11-7/8" (OSP)												
3009 Gutter Coil 11-7/8" (BSP)	•	•	•	•	•	•	•	•	•	•	•	•
3045 Gutter Coil 11-7/8" (OSP) Heavy Gauge												
3049 Gutter Coil 11-7/8" (BSP) Heavy Gauge	•	•	•	•	•	•	•	•	•	•	•	•
3012 Gutter Coil 13-1/2" (BSP)		•	•	•	•	•	•		•	•		
3084 Gutter Coil 6" (BSP)				•	•	•	•	•		•	•	

GENTEK VINYL SIDING AND SOFFIT

Produced to precise tolerances using formulated compounds specifically designed for the plastic building products industry according to ASTM D4216, meeting or exceeding the following:

Property	Test Method	Results
<i>Tensile Strength (psi)</i>	<i>ASTM D-638</i>	<i>6,700</i>
<i>Modulus of Elasticity (psi)</i>	<i>ASTM D-638</i>	<i>410,000</i>
<i>Izod Impact (70°F)</i>	<i>ASTM D-256</i>	<i>3.6 (ft-lb/in of notch)</i>
<i>Izod Impact (32°F)</i>	<i>ASTM D-256</i>	<i>2.0 (ft-lb/in of notch)</i>
<i>Flexural Strength (psi)</i>	<i>ASTM D-790</i>	<i>14,000</i>
<i>Coefficient of Linear Expansion</i>	<i>ASTM D-696</i>	<i>5.3 x 10⁻⁵ (mm/mm °C) 2.9 x 10⁻⁵ (in/in °F)</i>
<i>Deflection Temperature Under Load 264 psi (°C)</i>	<i>ASTM D-648</i>	<i>73</i>

PRODUCT PHYSICALS:

All siding products, soffit panels and accessories are made with solid colour throughout. The siding products and accessories meet or exceed the ASTM Specification for Rigid Poly Vinyl Chloride (PVC) Siding D3679. All soffit products and associated accessories meet or exceed the ASTM Specification for Rigid (Unplasticized) Poly Vinyl Chloride (PVC) Soffit D4477.

The siding and soffit compound meets Class 2 requirements and conforms to weathering performances as described in ASTM 3679.

Colour: Spectrophotometer controlled

Gloss: Gardner gloss meter controlled

Lock: Dimensionally controlled

All products meet or exceed ASTM 3679 thickness (nominal) requirements:

<i>Sequoia Select</i>	<i>0.046"</i>
<i>Board & Batten</i>	<i>0.050"</i>
<i>Easy Lock</i>	<i>0.041"</i>
<i>Fair Oaks</i>	<i>0.044"</i>
<i>Concord</i>	<i>0.042"</i>
<i>Driftwood II</i>	<i>0.040"</i>
<i>Oxford Premium Soffit</i>	<i>0.042"</i>
<i>Beaded Premium Soffit</i>	<i>0.042"</i>
<i>Fairweather Soffit</i>	<i>0.040"</i>

WARRANTY:

All Gentek vinyl siding brands carry a Lifetime Limited Warranty including fade and hail protection. *Warranty is transferable if the home is sold. See printed warranty for complete details.*

SOFFIT VENTILATION AREA:

Gentek soffit panels are designed to allow air circulation into the attic areas to aid in the reduction of excessive heat buildup and water vapor condensation. The net free open area (NFOA) per lineal foot of soffit is as follows:

10" Oxford Fully Vented	5.3 sq in
8" Easy Lock	2.8 sq in
8" Beaded Vented	2.4 sq in
12" Fairweather Fully Vented	7.1 sq in

FIRE RESISTANCE RATINGS:

Gentek vinyl siding products meet or exceed all building code requirements throughout the United States and Canada. In addition to meeting these code requirements, Gentek vinyl sidings have been fire rated by Underwriters Laboratories (UL) to be used in one-hour rated designed walls U026 and U032 and a two-hour rated wall, U301. UL inspects the manufacture of the vinyl products quarterly to certify that Gentek vinyl products are manufactured consistently. The vinyl products have been tested as follows:

Property	Test Method	Results
Average Burn Distance	ASTM D-635	20mm
Average Burn Time	ASTM D-635	<5 seconds
Flash Ignition Temperature	ASTM D-1929	752°F
Self Ignition Temperature	ASTM D-1929	860°F
Flame Spread Index	ASTM E-84	15
Flame Spread Index	CAN/ULC S102.2	25
Smoke Developed Index	ASTM E-84	<400
Fire Resistance	ASTM E-119	1-hour rated* 2-hour rated*

*See UL Fire Resistance Directory Control No. 1N60. E-119 is equivalent to UL-263 and E-84 is equivalent to UL-723.

Important fire safety information for the building trades, specifiers, professionals and do-it-yourself installers:

When rigid vinyl siding is exposed to significant heat or flame, the vinyl will soften, sag, melt, or burn and may thereby expose the material underneath. Care must be exercised when selecting underlay materials because many underlays are made from organics that are combustible. You should ascertain the fire properties of any underlay prior to installation. All building materials should be installed in accordance with local, state and federal building codes and fire regulations.

WINDLOAD PROPERTIES:

All Gentek siding products are designed to withstand a minimum of 100 mph windloads and are suitable for most areas. The products can be used in areas with higher windloads, but installation procedures, choice of product and building code jurisdiction are important factors to be considered. The windspeed rating (in mph) is calculated using VSI's windspeed calculation guidelines. Additional information is available if required.

BUILDING CODES:

Gentek vinyl products meet or exceed the following building code specifications:

ICC-ESR – 1133
CCMC – 06541-L
New York City MEA 132-94-M
FHA/HUD Minimum Property Standards

For architectural specifications of designer siding and other products, please see your local Gentek dealer.

GENTEK ALUMINUM SIDING AND SOFFIT**ALUMINUM METAL PROPERTIES:**

Alloy or equivalent.....	AA3000
Specific Gravity.....	2.72
Modulus of Elasticity (ksi).....	10,000
Melting Range (°F).....	1175-1210

COATING PROPERTIES: Gentek aluminum products are manufactured with AA3000 series alloy (or equivalent). Both sides of the aluminum are cleaned with a specially formulated cleaner. The cleaned aluminum is then treated with an acid solution containing chrome to enhance corrosion resistance and coating adhesion.

Polyester (Poly) Topcoat: The topside of the pretreated aluminum is coated with a thermoset polyester polymer which is dried and cured at about 450 °F, forming a hard but flexible and weatherable coating. Total coating thickness is approximately 18 micrometers.

WEATHERING AND TESTING: Gentek products are tested for superior adhesion and forming properties. Gentek's stringent colour specifications allow batch to batch mixing of product. Product testing includes colour, film thickness, gloss, hot water/impact test, freezer/impact test, salt spray, humidity testing (1000 hours) and outdoor exposure (2 years).

COMPLIANCE: The aluminum alloys used meet the ULC Standard CAN4-S114-M80, defining the noncombustibility of aluminum alloys.

WARRANTY: 40 Year Limited Warranty. Warranty is transferable.

CONTACT WITH DISSIMILAR MATERIALS AND CORROSIVE ENVIRONMENTS:

Direct contact of aluminum products with certain dissimilar materials, or contact with water runoff from dissimilar materials, is likely to result in corrosion. Accordingly, care should be taken during installation to avoid such contact of aluminum with dissimilar materials, including: dissimilar metals (copper, zinc, steel, etc.), concrete, stucco, asbestos siding, pressure treated/pretreated lumber, masonry, corrosive non-metallic materials, and roofing materials or roofing systems containing metallic granules or strips. Seacoast or other corrosive environments may result in corrosion of the product.

NOMINAL GAUGES (mm):

Product	Gauge
8" Horizontal.....	0.53
D4 Dutch Lap.....	0.40
D4 Clapboard.....	0.40 and 0.44
8" Vertical Board & Batten.....	0.50
Vertical "V".....	0.40
16" Soffit – 2 Panel.....	0.29 and 0.38
16" Soffit – 4 Panel.....	0.29 and 0.38
18" Soffit – 3 Panel.....	0.33
4" Fascia – rib.....	0.44
6" Fascia – rib and non-rib.....	0.44 and 0.50
8" Fascia – rib and non-rib.....	0.44 and 0.50
Gutter Coil.....	0.57, 0.66 and 0.79

SOFFIT VENTILATION AREA:

Gentek soffit is available in a variety of profiles. Vented panels are designed to allow air circulation into the attic areas to aid in the reduction of excessive heat build-up and water vapour condensation.

PROFILE	PER LINEAR FOOT	PER PANEL
16" – 2 panel	4.02 sq in (26.0 cm ²)	48.7 sq in (314.00 cm ²)
16" – 4 panel	4.12 sq in (26.6 cm ²)	51.25 sq in (330.64 cm ²)
18" – 3 panel	5.46 sq in (35.2 cm ²)	54.6 sq in (352.26 cm ²)

VENTILATION: Fully vented

GENTEK STEEL SIDING

METAL PROPERTIES:

Steel or Equivalent	AZ-50
Specific Gravity	7.8
Minimum Ultimate Strength (KSI)	45-55
Minimum Yield (KSI)	40-50
Minimum Elongation (%)	25-35
Modulus of Elasticity (KSI)	29,500
Coefficient of Thermal Expansion (in/in °F)	0.000006
Melting Range (°F) Steel	>2700
Melting Range (°F) Zinc	786
Thermal Conductivity at 77°F (btu-in/ft ² -hr-°F)	555

COATING PROPERTIES:

Gentek steel siding products are manufactured with AZ-50. Both sides of the steel sheet are cleaned with a specially formulated cleaner, water rinsed and then coated with an environmentally safe chemical pretreatment to enhance corrosion protection and coating adhesion.

The pretreated surface is coated with a thermoset corrosion-resistant polymer. This corrosion-resistant polymer is topcoated with the following polymeric systems:

Plastisol (PVC) Topcoat: This highly weatherable, flexible, chemical-resistant thermoplastic polymer is melted and fused at temperatures of >390°F. The coating is applied with a striated pattern or smooth finish having an average film thickness of 3.0 mils.

Fluoropolymer (PVDF₂): This thermoplastic polymer has excellent chemical and fade resistance. The coating thickness is 0.9 mil. The system is cured at a minimum temperature of 475°F. This polymer system conforms to the high industry standards of Kynar 500® and Hylar 5000®. The main criteria for these standards is that the paint formulation must contain a minimum of 70% PVDF₂. Many fluoropolymer coatings on the market do not meet the high quality and performance standards required by Kynar 500 and Hylar 5000 specifications.

WARRANTY:

All Gentek steel siding brands carry a Lifetime Limited Warranty. *Warranty is transferable if home is sold. See printed warranty for complete details.*

CONTACT WITH DISSIMILAR MATERIALS:

Direct contact of steel products with certain dissimilar materials, or contact with water runoff from dissimilar materials, is likely to result in corrosion. Accordingly, care should be taken during installation to avoid such contact of steel with dissimilar materials, including: dissimilar metals (copper, zinc, steel, etc.), concrete, stucco, asbestos siding, pressure treated/pretreated lumber, masonry, corrosive non-metallic materials, and roofing materials or roofing systems containing metallic granules or strips.

PRODUCT PHYSICALS:

Product	Coating Type	Thickness*
Sierra Steel	PVDF ₂	0.017
SteelSide	PVC	0.017

*29 Gauge

BUILDING CODES:

Gentek steel products meet or exceed the following building code specifications:

ICC-ES Legacy – Report #97-64

AAMA 1406-86

FHA/HUD Minimum Property Standards

GENTEK ALIGN COMPOSITE CLADDING**PHYSICAL DATA:**

Colour Uniformity is spectrophotometrically controlled
Emboss Cedar mill grain (7" Plank and 12" Board & Batten);
Matte (12" Board & Batten)
Gloss Uniform low gloss maintained with a 75° gloss meter

PRODUCT TEST DATA:

Impact Resistance	>35 inch lbs
Coefficient of Linear Expansion (in/in/°F)	2.3×10^{-5}
Thermal Resistance	R-value 2.0 (7" Plank)
Thermal Resistance	R-value 1.6 (12" Board & Batten)
ASTM D5206-13, Windload Resistance	7" Plank – 53 psf (24" OC nails, 1-1/4" penetration) 12" Board & Batten – 52 psf (12" OC nails; 65.33 psf (8" OC nails)

FIRE RESISTANCE:

CAN/ULC S102.2-18	Flame spread rating > 70 Smoke developed classification > 470
ASTM E2707-22, Rated Assemblies	Approved for use
ASTM E119, Rated Assemblies	Approved for use
ASTM D635, Rate of Burn	No self-sustained burn
ASTM D1929, Self-Ignition/Flash-Ignition Temperature	770°F (410°C)/734°F (390°C)
NFPA 268, Section 1406 of IBC	Approved for use

CODES AND REGULATORY COMPLIANCE:

Intertek Code Compliance Research Report #0316
ICC-ES Evaluation Report – ESR 4449
Florida Product Approval #31747 (7" Plank); #46921(12" Board & Batten)

WARRANTY:

ALIGN offers a lifetime limited warranty to the original homeowner; the warranty is transferable if the home is sold.

THREE-PART FORMAT SPECIFICATION:

Long-form specification in three-part format is available at www.gentek.ca/align

COMPOSITE CLADDING | COLOUR PALETTE

Snow White	Dover Gray	Rockwell Blue
Almond	Chesapeake Gray	Midnight Surf
Monterey Sand	Storm	Marine Dusk
Pebble	Hudson Slate	Meadow Fern
Dark Drift	Windswept Smoke	Moonlit Moss
Rockport Brown	Iron Ore	Majestic Brick
Smoked Timber	Coastal Blue	

VINYL COLOUR PALETTE

Classic Colours

Snow White	Canyon Clay	Dover Gray
Sandstone	Pebble	Storm
Linen	Monterey Sand	Chesapeake Gray
Almond	Amber	Sage
Maize	Pearl	Juniper Grove
Wicker		

Designer Colours

Majestic Brick	Meadow Fern	Marine Dusk
Dark Drift	Moonlit Moss	Hudson Slate
Rockport Brown	Rockwell Blue	Windswept Smoke
Espresso	Coastal Blue	Iron Ore
Musket Brown (soffit only)	Midnight Surf	Black (soffit only)
Smoked Timber		

ALUMINUM | COLOUR PALETTE

Bright White	Rockport Brown	Wedgewood Blue
Rainware White	Smoked Timber	Midnight Surf
Ice White	Metallic Gray	Coastal Blue
White 701	Pearl	Old World Blue
Sandstone	Dover Gray	Marine Dusk
Cashmere	Storm	AluCopper
Almond	Chesapeake Gray	Burgundy
Maize	Slate	Majestic Brick
Wicker	Hudson Slate	Nutmeg
Canyon Clay	Windswept Smoke	Chestnut Brown
Pebble	Sage	Commercial Brown
Monterey Sand	Meadow Fern	Antique Brown
Lambeth Beige	Moonlit Moss	Espresso
Tan	Ivy Green	Graphite
Brownstone	Forest Green	Iron Ore
Dark Drift	Rockwell Blue	Black
Sable		

ALUMINUM | COLOUR MATCH

James Hardie Colour Match Gentek Colour [James Hardie Colour]

Bright White [Arctic White]	Ash Gray [Iron Gray]	Desert Sand [Monterey Taupe]
Stone Gray [Pearl Gray]	Almond [Navajo Beige]	Barn Brown [Timber Bark]
Pewter [Aged Pewter]	Fieldstone [Cobblestone]	

CanExcel Colours

White XL	Khaki	Cedar XL
Green	Country Red XL	

STEEL COLOUR PALETTE

Sierra Steel Colours

Bright White	Sable	Iron Ore
Chelsea Bluff	Juniper Grove	Rockwell Blue
Monterey Sand	Dover Gray	Watermill Blue
Delray Sand	Storm	Taylor Red
Thistle		

SteelSide Colours

Bright White	Brownstone	Sage
Almond	Norwood	Pacific Blue
Wicker	Thistle	Dover Gray
Canyon Clay	Sable	

gentek.ca



GENTEK[®]
GENTEK BUILDING PRODUCTS CO.

1001 Corporate Drive
Burlington, ON L7L 5V5

Make us a part of your home.

Not all products and colours are available all locations. Please check with your local Gentek branch for product availability. Colours may be slightly different from their appearance in this brochure. Make final colour selections using actual product samples. Product Improvement Policy: Gentek Building Products Company is constantly improving product designs and manufacturing processes. We therefore must reserve the right to change specifications without notice. Please consult Gentek Building Products Company for current details. Trademarks mentioned in this document are the property of Gentek Building Products Company, its affiliates or their respective owners. Accessible formats and communication supports available upon request.

Effective Date: March 2026

